Revision Date: 07/26/2022

Section 1. Product and Company Identification

Product Identifier Ballistic Compound

Product Use

Description: Viscous White lotion with fruity odor for use as a automotive polishing compound

Manufacturer or suppliers' details

Finish First Auto Products, Inc.

6700 NE 152nd Ave,

Suite 200

Vancouver, WA 9868

Technical Phone Number: 1-800-998-9208

24 HR. EMERGENCY TELEPHONE NUMBER

INFOTRAC: +1.800.535.5053

Section 2. Hazards Identification

GHS Classification

Flammable Liquids : Category 4

Skin Corrosion: Category 3 **Eye Irritation**: Category 2A

Acute Toxicity: Category 5 (oral)
Acute Toxicity: Category 5 (inhalation)

Acute Toxicity: Category 5 (dermal)

GHS Label Elements

Hazard Pictograms



Hazard Word Warning

Hazard Statements

H227: Combustible liquid

H303: May be harmful if swallowed

H313: May be harmful in contact with skin

H319: Causes serious eye irritation

H333: May be harmful if inhaled

Precautionary Statements

P101: If medical advice is needed, have product container or label at hand

P102: Keep out of reach of children

P103: Read label before use

P210: Keep away from heat/sparks/open flames/hot surfaces - No smoking Wear

P280: protective gloves/protective clothing/eye protection/face protection Wash

P264: skin thoroughly after handling

P301+312: IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P304+312: IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell

P340: Remove victim to fresh air and keep at rest in a position comfortable for

breathing.

Ballistic Compound

Page

Revision Date: 07/26/2022

P305+351+338:

P337+313: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact

P370+378: lenses if present and easy to do – continue rinsing

P403+235: If eye irritation persists: Get medical advice/attention In case of fire: Use Dry Chemical, Foam of CO2 for extinction

P501: Store in a well ventilated place. Keep cool

Dispose of contents/container to an approved waste disposal plant.

3. Composition Information on Ingredients

CAS Number	Wt %	Component Name
88551-19-9	50-100	Isoalkanes
732-18-5	<15	Water
60828-78-6	<8	Propylene Glycol Trimethylnonyl Ether
1344-38-1	<30	Aluminum Oxide
61790-53-2	<15	Diatomaceous Earth (de) - Amorphous Silica
68155-20-4	<4	Amides

Amounts specified are typical and do not represent a specification. Remaining components are proprietary, non-hazardous, and/or present at amounts below reportable limits.

4. First Aid Measures

EYE CONTACT

If splashed into the eyes, flush with clear water for 15 minutes or until irritation subsides. If irritation persists, call a physician.

SKIN

In case of skin contact, remove any contaminated clothing and wash skin with soap and water. Launder or dry-clean clothing before reuse. If product is injected into or under the skin, or into any part of the body, regardless of the appearance of the wound or its size, the individual should be evaluated immediately by a physician as a surgical emergency. Even though initial symptoms from high pressure injection may be minimal or absent, early surgical treatment within the first few hours may significantly reduce the ultimate extent of injury.

INHALATION

If overcome by vapor, remove from exposure and call a physician immediately. If breathing is irregular or has stopped, start resuscitation, administer oxygen, if available.

INGESTION

If ingested, **DO NOT** induce vomiting; call a physician immediately.

5. Fire Fighting Measures

EXTINGUISHING MEDIA AND FIRE FIGHTING PROCEDURES

Foam, water spray (fog), dry chemical, carbon dioxide and vaporizing liquid type extinguishing agents may all be suitable for extinguishing fires involving this type of product, depending on size or potential size of fire and circumstances related to the situation. Plan fire protection and response strategy through consultation with local fire protection authorities or appropriate specialists.

Use dry chemical, foam or carbon dioxide to extinguish the fire. "Water may be ineffective", but water should be used to keep fire-exposed containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect persons attempting to stop a leak. Water spray may be used to flush spills away from exposures. Minimize breathing of gases, vapor, fumes or decomposition products. Use supplied-air breathing equipment for enclosed or confined spaces or as otherwise needed.

DECOMPOSITION PRODUCTS UNDER FIRE CONDITIONS

Fumes, smoke, carbon monoxide, sulfur oxides, aldehydes and other decomposition products, in the case of incomplete combustion.

Revision Date: 07/26/2022

6. Accidental Release Measures

Precautions Required if Material is Released or Spilled:

Evacuate area of all unnecessary personnel. Wear protective equipment and/or garments described in Section C if exposure conditions warrant. Shut off source, if possible and contain spill. Protect from ignition. Keep out of water sources and sewers. Absorb in a dry, inert material (sand, clay, etc). Transfer to disposal drums using non-sparking equipment.

Waste Disposal (Insure Conformity with all Applicable Disposal Regulations): Incinerate or place in permitted waste management facility.

7. Handling and Storage

Do not swallow, may be aspirated into lungs. Avoid contact with eyes, skin or clothing. Avoid breathing vapors, mist, fume or dust. Wear protective equipment and/or garments described in Section C if exposure conditions warrant. Wash thoroughly after handling. Launder contaminated clothing before reuse. Use with adequate ventilation. Keep away from heat, sparks and flame. Store in well-ventilated area. Store in tightly closed container. Bond and ground during transfer.

8. Exposure Controls and Personal Protection

88551-19	-9 Isoalkanes	1200 mg/m3, TWA, Manufacturer
732-18-5	Water	None Established
60828-78	-6 Propylene Glycol Trimethylnonyl Ether	None Established
1344-38-	1 Aluminum Oxide	None Established
61790-53	-2 Diatomaceous Earth (de) - Amorphous	.025 mg/m3 Respirable Cristobalite ACGIH
	Silica	
68155-20	-4 Amides	None Established

VENTILATION

Use only with ventilation sufficient to prevent exceeding recommended exposure limit or buildup of explosive concentrations of vapor in air. No smoking, or use of flame or other ignition sources.

RESPIRATORY PROTECTION

Not generally requirted. Use supplied-air respiratory protection in confined or enclosed spaces, if needed.

PROTECTIVE GLOVES

Use chemical-resistant gloves, if needed, to avoid prolonged or repeated skin contact.

EYE PROTECTION

Use splash goggles or face shield when eye contact may occur.

OTHER PROTECTIVE EQUIPMENT

Use chemical-resistant apron or other impervious clothing, if needed, to avoid contaminating regular clothing, which could result in prolonged or repeated skin contact.

WORK PRACTICES / ENGINEERING CONTROLS

To prevent fire or explosion risk from static accumulation and discharge, effectively bond and/or ground product transfer system in accordance with (THE) National Fire Protection Association PUBLICATIONS.

Revision Date: 07/27/2022

9. Physical and Chemical Properties

Flash Point >92°C Upper Flamability Limit not established

Auto Ignition no data available Lower Flamability Limit not established

Physical State Liquid Color White Vapor Press no data available

pH 8 Specific Gravity 1.10 Viscosity 2500 cst

Vapor Density (Air=1) >3 Melting Point °F N/D Odor fruity

Water Solubility partially dispersable VOC Content 3.46 lb/Gal see Section 15 for

Details

10. Stability and Reactivity

Stability Stable Hazardous Polymerization Not Expected to Occur

Conditions to Avoid Keep away from extreme heat, Strong Acids, Alkalies and Oxidizers such as

Chlorine, other Halogens, Hydrogen Peroxide and Oxygen

Hazardous No substances are readily identifiable from composition but no degradation

Decomposition Products data is available.

11. Toxicological Information

NATURE OF HAZARD AND TOXICITY INFORMATION

Prolonged or repeated skin contact with this product tends to remove skin oils, possibly leading to irritation and dermatitis; however, based on human experience and available toxicological data, this product is judged to be neither a "corrosive" nor an "irritant" by OSHA criteria.

Acute Toxicity

Polyethylene Glycol Trim Oral Rat Ld 50 3,300 Mg/kg

Polyethylene Glycol Trim Inhalation - No Data Available

Polyethylene Glycol Trim Dermal Rabbit Ld 50: 8,874 Mg/kg

Isoalkanes Oral Rat Ld 50 > 5 Mg/l

Isoalkanes Inhalation Rat Lc 50 > 5.3 Mg/l

Isoalkanes Dermal Rabbit Ld 50 > 2 Mg/kg

Amids Alkanolamide Oral Mouse Ld 50 > 2200 Mg/kg

Amids Alkanolamide Inhalation - No Data Available

Amids Alkanolamide Dermal Rabbit Ld 50 > 12200 Mg/kg

12. Ecological Information

Do not discharge this product into public waters or waterways unless authorized by a National Pollution Discharge Elimination System (NPDES) permit issued by the Environmental Protection Agency (EPA).

13. Disposal Considerations

Options for disposal of this product may depend on the conditions under which it was used. To determine the proper method of disposal, refer to RCRA (40 CFR 261), as well as federal EPA and state and local regulations.

Please refer to Sections 5, 6 and 15 for additional information.

Page :

Revision Date: 07/26/2022

14. Transportation Information

Domestic Transportation, not by air:

Non-bulk packagings (capacity less than or equal to 119 gallons)

Not regulated - Reclassified as combustible 49 CFR 173.150(f)

Transported by marine vessel:

Non-bulk packagings (capacity less than or equal to 119 gallons)

Not regulated - Reclassified as combustible 49 CFR 173.150(f)

Transportation by Air IATA:

Limited Quantity exception: 49 CFR 173.150(b)(3), 173.27 table 3 - Combination packaging under 5 Liter or 1.3 gallon per inner container and less than 10 liters per box

Not Regulated

Packaging greater than 5 Liter or 1.3 Gallon per inner container or more than 10 liters per box UN1993, Flammable Liquid n.o.s. (Naphtha Solvent), 8, PGIII

15. Regulatory Information

OSHA Hazards: Moderate skin Irritant, Chronic Health Hazard

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity - This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards: Acute Health Hazard, Chronic Health Hazard

SARA 302: No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65: Is Product Does Not Contain Chemicals Known To The State Of California To Cause Cancer.

Clean Air Act (CAA) -

This product does not contain any hazardous air pollutants (HAP), as defined by the U.S. Clean Air Act Section 12 (40 CFR 61).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 112(r) for Accidental Release Prevention (40 CFR 68.130, Subpart F).

This product does not contain any chemicals listed under the U.S. Clean Air Act Section 111 SOCMI Intermediate or Final VOC's (40 CFR 60.489)

Clean Water Act -

This product does not contain any Hazardous Substances listed under the U.S. CleanWater Act, Section 311, Table 116.4A.

This product does not contain any Hazardous Chemicals listed under the U.S. Clean- Water Act, Section 311, Table 117.3.

This product does not contain any toxic pollutants listed under the U.S. Clean Water Act Section 307

ARB VOC info: 14.5% VOC as regulated by CARB Consumer Products requirements, LVP-VOC

exception

AQMD VOC Info: 3.46 lb/gal VOC 396 g/L

Revision Date: 07/26/2022

16. Other Information

Revision Date 12/20/2017

The information and recommendations are offered for the user's consideration and examination, and it is the user's responsibility to satisfy itself that they are suitable and complete for its particular use. If buyer repackages this product, legal counsel should be consulted to insure proper health, safety and other necessary information is included on the container.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH American Conference of Government Industrial Hygienists

LD50 Lethal Dose 50%

AICS Australia, Inventory of Chemical Substances

LOAEL Lowest Observed Adverse Effect Level

DSL Canada, Domestic Sub- stances List

NFPA National Fire Protection Agency

NDSL Canada, Non-Domestic Sub- stances List

NIOSH National Institute for Occupational Safety & Health

CNS Central Nervous System

NTP National Toxicology Program

CAS Chemical Abstract Service

NZIoC New Zealand Inventory of Chemicals

EC50 Effective Concentration

NOAEL No Observable Adverse Effect Level

EC50 Effective Concentration 50%

NOEC No Observed Effect Concentration

EGEST EOSCA Generic Exposure Scenario Tool

OSHA Occupational Safety & Health Administration

EOSCA European Oilfield Specialty Chemicals Association

PEL Permissible Exposure Limit

EINECS European Inventory of Exist- ing Chemical Substances

PICCS Philipines Inventory of Commercial Chemical Substances

MAK Germany Maximum Concentration Values

PRNT Presumed Not Toxic

GHS Globally Harmonized System

RCRA Resource Conservation Recovery Act

>= Greater Than or Equal To

STEL Short-term Exposure Limit

IC50 Inhibition Concentration 50%

SARA Superfund Amendments and Reauthorization Act.

IARC International Agency for Re- search on Cancer

TLV Threshold Limit Value

IECSC Inventory of Existing Chemical Substances in China

TWA Time Weighted Average

ENCS Japan, Inventory of Existing and New Chemical Sub- stances

TSCA Toxic Substance Control Act

KECI Korea, Existing Chemical Inventory

UVCB Unknown or Variable Composition, Complex Reaction Products, and Biological Materials <= Less Than or Equal To

WHMIS Workplace Hazardous Materials In- formation System

LC50 Lethal Concentration 50%