

# SAFETY DATA SHEET



## ClearMax™ Pro All-Temp

Date Prepared : 10/11/2023  
 MSDS No : FFAA-CMP-AT  
 Date-Revised : 10/11/2023  
 Revision No : 1

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** ClearMax™ Pro All-Temp  
**ALTERNATE TRADE NAME(S):** None

#### MANUFACTURER

FinishFirst Auto Products

P.O. Box 2249

Vancouver, WA 98668-2249

Customer Service: +1.800.998.9208

**24 HR. EMERGENCY TELEPHONE NUMBERS**

**INFOTRAC : +1.800.535.5053**

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Flammable Liquids, Category

#### 3 GHS LABEL



Flame

**SIGNAL WORD:** WARNING

#### HAZARD STATEMENTS

**H226:** Flammable liquid and vapour.

#### PRECAUTIONARY STATEMENT(S)

##### Prevention:

**P261:** Avoid breathing dust/fumes/gas/mist/vapours/spray.

**P270:** Do not eat, drink or smoke when using this product.

**P240:** Ground/bond container and receiving equipment.

**P403+P233:** Store in a well-ventilated place. Keep container tightly closed.

#### EMERGENCY OVERVIEW

##### IMMEDIATE CONCERNS:

**WARNING!** Flammable liquid and vapor. Eye, skin and respiratory tract irritant. May be harmful if inhaled or absorbed through skin.

**ClearMax™ Pro All-Temp****POTENTIAL HEALTH EFFECTS**

**EYES:** Irritant. May cause redness, irritation and/or pain.

**SKIN:** May be harmful if absorbed through the skin. Irritant. May cause redness, inflammation or dermatitis.

**INGESTION:** May be irritating to digestive tract; may cause gastric distress, stomach pains.

**INHALATION:** May be harmful if inhaled. May cause respiratory tract irritation. May produce symptoms of central nervous system depression, including headache, dizziness, nausea, loss of balance, and drowsiness.

**CARCINOGENICITY:** Not listed as a carcinogen by the NTP, IARC, or OSHA.

**MEDICAL CONDITIONS AGGRAVATED:** No information found.

**3. COMPOSITION / INFORMATION ON INGREDIENTS**

<b>Ingredient name</b>	<b>Average %</b>	<b>CAS Number</b>
Methyl (n-amyl) ketone	30.625	110-43-0
2-Butoxyethyl Acetate	13.125	112-07-2
Toluene	8.750	108-88-3
n-Butyl acetate	13.125	123-86-4
Isopropyl acetate	10.938	108-21-4
Acetone	7.219	67-64-1
Methyl Isobuty Ketone	3.063	108-10-1
xylene	2.875	98-56-6
acetone	1.875	1330-20-7
Solvent naphtha (petroleum), light aromatic	0.394	67-64-1
ethylbenzene	0.375	64742-95-6
toluene	0.375	100-41-4
Ligroine	0.375	108-88-3
1,2,4-trimethylbenzene	0.306	8032-32-4
heptan-2-one	0.022	95-63-6
cumene	0.125	110-43-0
Total Active:	93.566	N/A
Ingredients Not Required to be Listed*	6.434	N/A

*\*There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.*

Any concentration shown as a range is to protect confidentiality or is due to batch variation.

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section. Occupational exposure limits, if available, are listed in Section 8.

**4. FIRST AID MEASURES**

**EYES:** Immediately flush eyes with plenty of water for at least 15 minutes while holding eyelids open. Get medical attention, if irritation occurs or persists.

**SKIN:** Remove contaminated clothing/shoes. Flush skin with water for at least 15 minutes. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

**INGESTION:** If swallowed, DO NOT induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Seek immediate medical attention.

**NOTES TO PHYSICIAN:** All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Treat symptomatically. No specific antidote available.

**ClearMax™ Pro All-Temp****5. FIRE FIGHTING MEASURES**

**EXTINGUISHING MEDIA:** Foam, carbon dioxide, dry chemical.

**6. ACCIDENTAL RELEASE MEASURES**

**SMALL SPILL:** Absorb liquid on vermiculite, floor absorbent, or other absorbent material, then place in container for chemical waste. Flush spill area with water spray. Prevent run-off from entering drains, sewers or streams.

**7. HANDLING AND STORAGE**

**GENERAL PROCEDURES:** Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Use in well ventilated areas.

**STORAGE:** Store in a cool, dry, ventilated area, away from incompatible substances.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**ENGINEERING CONTROLS:** Local exhaust and general ventilation must be adequate to meet exposure limit(s).

**PERSONAL PROTECTIVE EQUIPMENT**

**EYES AND FACE:** Chemical goggles/face shield.

**SKIN:** Gloves resistant to chemicals and petroleum distillates must be worn. Neoprene, butyl rubber, or polyethylene.

**COMMENTS:** Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**PHYSICAL STATE:** Liquid

**ODOR:** Faint aromatic hydrocarbon odor.

**pH:** Not determined.

**FLASHPOINT AND METHOD:** 42.8°C (109°F) TAG CC

**FLAMMABLE LIMITS:** 0.9% to 10.5%

**AUTOIGNITION TEMPERATURE:** > 500°C (932°F)

**VAPOR PRESSURE:** 5.3 mm Hg at 20°C

**VAPOR DENSITY:** 6.2

**BOILING POINT:** 139°C (282°F)

**FREEZING POINT:** -33°C (-36°F)

**SOLUBILITY IN WATER:** Slight

**EVAPORATION RATE:** 0.9

**SPECIFIC GRAVITY:** 1.34

**VISCOSITY:** Not specified.

**MOLECULAR WEIGHT:** 180.56 **Formula:** C7H4CIF3

**10. STABILITY AND REACTIVITY**

**HAZARDOUS POLYMERIZATION:** Will not occur under normal conditions.

**STABILITY:** Stable under normal conditions.

**CONDITIONS TO AVOID:** Oxidizing materials.

## ClearMax™ Pro All-Temp

**11. TOXICOLOGICAL INFORMATION****12. ECOLOGICAL INFORMATION****AQUATIC TOXICITY (ACUTE)**

**48-HOUR EC<sub>50</sub>:** 10.7 mg/l (Daphnia)

**CHEMICAL FATE INFORMATION:** No data found for product.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** Product, as supplied, meets the characteristics of a ignitable hazardous waste as defined in 40 CFR 261.21-24. If mixed with other products, waste mixture must be characterized. DO NOT dispose of the product in drains or storm sewers. DO NOT dispose of this product in landfill without prior solidification. Waste product should be recycled whenever possible. Any disposal practice must be in compliance with federal, state, and local regulations. Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

**EMPTY CONTAINER:** KEEP OUT OF REACH OF CHILDREN! Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

**RCRA/EPA WASTE INFORMATION:** Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR. Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

**14. TRANSPORT INFORMATION****DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Chlorobenzotrifluorides

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** UN2234

**PACKING GROUP:** III

**NAERG:** 130

**LABEL:** Flammable liquid

**15. REGULATORY INFORMATION****UNITED STATES****DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**

Flammable  
Liquid

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**ClearMax™ Pro All-Temp**

**311/312 HAZARD CATEGORIES:** This product should be reported as a fire hazard.

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** No **CHRONIC:** No **313**

**REPORTABLE INGREDIENTS:** To the best of our knowledge, this product is not listed as a toxic chemical under Section 313 of SARA Title III.

**302/304 EMERGENCY PLANNING**

**EMERGENCY PLAN:** To the best of our knowledge, this product is not listed as an extremely hazardous substance.

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

**TSCA STATUS:** Listed.

**CALIFORNIA PROPOSITION 65:** To the best of our knowledge this material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

**CANADA**

**DOMESTIC SUBSTANCE LIST (INVENTORY):** Not Controlled.

**16. OTHER INFORMATION**


**REASON FOR ISSUE:** Updated SDS information and changed to new format.

**PREPARED BY:** COMPLIANCE **Date-Revised:** 01/18/2022

**REVISION SUMMARY:** New Product

**HMIS RATING**

<b>HEALTH</b>	<input type="checkbox"/>	<b>1</b>
<b>FLAMMABILITY</b>	<input type="checkbox"/>	<b>2</b>
<b>PHYSICAL HAZARD</b>	<input type="checkbox"/>	<b>0</b>
<b>PERSONAL PROTECTION</b>	<input type="checkbox"/>	

**NFPA CODES**

**MANUFACTURER DISCLAIMER:** The information contained herein is based on the data available to us and is believed to be accurate. However, FinishFirst Auto Procuts (FFAP) makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. FFAP assumes no responsibility for injuries from the use of the product described herein.