

Section 1: Identification

Product Identification: FinalFinish

Company: FinishFirst Auto Products

Address: 12511 NE Fourth Plain Rd, Vancouver WA 98682, United States

Phone: 800-998-9208

Function or use category: Wipe-on coating for automotive plastic and painted surfaces.

Emergency Phone: 1-800-535-5053

Section 2: Hazard(s) Identification

Flammable Liquid. Category 3

DANGER



HAZARD STATEMENTS:

H226:	Flammable liquid & vapor	Category 3
H304:	May be fatal if swallowed and enters airways.	Category 1
H373:	May cause damage to cardiovascular system and central nervous system through prolonged or repeated exposure.	Category 2 N/A
H315:	Causes skin irritation,	Category 2
H320:	Causes eye irritation,	Category 2B
H335:	May cause respiratory irritation,	Category 3
H336:	May cause drowsiness or dizziness,	N/A
H361:	Suspected of damaging fertility or the unborn child if inhaled,	Category 2
H251:	Self-heating; may catch fire	N/A

PRECAUTIONARY STATEMENTS:

P201: Obtain special instructions before use.

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

SDS FinalFinish

Date: 06/01/2016 Page 2 of 8

(Section 2 Continued) **PRECAUTIONARY STATEMENTS:**

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302: IF ON SKIN:

P352: Wash with soap & water.

P361: Take off immediately all contaminated clothing.

P362: Take off contaminated clothing.

P363: Wash contaminated clothing before reuse.

P304 IF INHALED:

P340: Remove person to fresh air and keep comfortable for breathing.

P305: IF IN EYES:

351: Rinse cautiously with water for several minutes.

338: Remove contact lenses if present & easy to do - Continue rinsing.

P301: IF SWALLOWED:

310: Immediately call a POISON CENTER or doctor/physician.

Section 3: Composition/Information on Ingredients

CHEMICAL NAMES	COMMON NAMES	CAS No.	EINECS No.	% W*	CLP CLASS
Hydrodesulfurized naphtha	High Boiling White Spirit	64742-82-1	265-185-4	<50	Skin Irrit. 2; H315 STOT RE 1; H372 , Aquatic Chronic 2; H411
Hydrotreated light distillate	light Petroleum Distillate	64742-47-8	265-149-8	<50	Asp. Tox. 1, H304 (CLP) Flam. Liq. 3, H226; STOT SE 3, H336;
Stoddard solvent	Aliphatic Petroleum Distillates	8052-41-3	232-489-3	<50	Carc.Cat.1; R45 Muta.Cat.1; R46 Xn; R65
medium aliphatic hydrocarbon	Naphtha	64742-88-7	232-455-8	<13	Flam. Liq. 3, H226 Skin Irrit. 2, H315 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
Benzene, Ethylmethyl	Ethylmethylbenzene	25550-14-5	247-093-6	<3	Flam. Liq. 3, H226; Asp. Tox. 1, H304; STOT SE 3, H336

Trimethylbenzene	methylxylene	25551-13-7	247-099-9	<0.75	Acute Tox.4(Oral), H302 Skin Irrt. 2, H315 Eye Irrt. 2B, H320 Asp. Tox. 1, H304
------------------	--------------	------------	-----------	-------	---

SDS FinalFinish

Date: 06/01/2016 Page 3 of 8

(Section 3 Continued)

Xylene {Benzene, dimethyl-}	Xylol	1330-20-7	215-535-7	<0.5	Flam. Liq. 3, H226, Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Skin Irrt. 2, H315
Cobalt Naphthenate	Naphthenic acids. Cobalt salts	61789-51-3	263-064-0	<1	Flam. Sol. 2;H228, Skin Sens. 1;H317, Resp. Sens. 1;H334, Carc. 2;H351, STOT RE 2;H373
Trade Secret Polymer Resin Mixture	No Data	No Data	No Data	<40	Flam. Liq. 3, Skin Sens. 1, STOT SE 3, STOT RE 2; Asp. Tox. 1, H315, H319, H226, H317, H304, H335, H336, H373

*The specific chemical identity and exact percentage (concentration) of composition has been withheld as a trade secret.

Trace components: Trace ingredients (if any) are present in < 1% concentration, (< 0.1% for potential carcinogens, reproductive toxins, respiratory tract mutagens, and sensitizers). None of the trace ingredients contribute significant additional hazards at the concentrations that may be present in this product.

Section 4: First-Aid Measures

SKIN CONTACT: Wash with soap and water. Flush with water. Minimum flushing is for 15 minutes. Remove contaminated clothing, taking care not to contaminate eyes. If skin becomes irritated and irritation persists, get medical attention. Wash contaminated clothing before reuse, discard contaminated shoes or articles that are unable to be thoroughly cleaned and free of contamination..

EYE CONTACT: If this product enters the eyes, open eyes while under gently running water. "Roll" eyes to expose more surface. Minimum flushing is for 15 minutes. Seek immediate medical attention.

INHALATION: Move to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention.

SWALLOWING: If swallowed, CALL PHYSICIAN OR POISON CONTROL CENTER FOR MOST CURRENT INFORMATION. If professional medical advice is not available, give two glasses of water to drink. DO NOT INDUCE VOMITING. Never induce vomiting or give liquids to someone who is unconscious, having convulsions, or unable to swallow. Seek immediate medical attention.

NOTES TO PHYSICIAN: Move to fresh air. If breathing is difficult, give oxygen. If breathing has stopped, trained personnel should immediately begin artificial respiration. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband. If the heart has stopped, trained personnel should immediately begin cardiopulmonary resuscitation (CPR). Seek immediate medical attention. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.

Section 5: Fire-Fighting Measures

PREVENTIVE MEASURES: No smoking. Keep away from ignition sources, open flame, sparks, etc. Keep below flash point. Keep away from heat sources. Keep in tightly closed container. Saturated materials should be allowed to dry with no wading, folding, or stacking to avoid excessive heat and possible spontaneous combustion. Flash point: 101F, 38C

EXTINGUISHING MEDIA: Use dry powder, foam, carbon dioxide.

SPECIAL FIRE FIGHTING PROCEDURES AND EQUIPMENT: Water spray may be ineffective on fire but can protect fire-

fighters & cool closed containers. Use fog nozzles if water is used. Do not use direct stream of water, product will float and can be reignited on surface. Use water spray to cool fire exposed containers to prevent vapor pressure build up. UNUSUAL EXPLOSION AND FIRE PROCEDURES COMBUSTIBLE! Isolate from oxidizers, heat, & open flame. Closed containers may explode if exposed to extreme heat. Empty container very hazardous! Follow all label precautions! Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode

Section 6: Accidental Release Measures

SPILL AND LEAK RESPONSE AND PRECAUTIONS: Uncontrolled releases should be responded to by trained personnel using pre-planned procedures. Proper protective equipment should be used. In case of a spill, alert trained personnel, protect people, clear the affected area. Extinguish or turn off all ignition sources. Ventilate the involved space. Saturated materials should be allowed to dry with no wading, folding, or stacking to avoid excessive heat and possible spontaneous combustion.

PERSONAL PROTECTIVE EQUIPMENT: For small small releases, such as a single 32oz can, use impermeable gloves, Self-Contained Breathing Apparatus specific for the material handled, goggles, face shield, and appropriate body protection. In the event of a large release, use impermeable gloves, specific for the material handled, chemically resistant suit and boots, and hard hat. Self-Contained Breathing Apparatus or respirator may be required where engineering controls are not adequate or conditions for potential exposure exist. When respirators are required, select NIOSH/MSHA approved based on actual or potential airborne concentrations in accordance with latest OSHA and/or ANSI recommendations.

ENVIRONMENTAL PRECAUTIONS: Stop spill at source. If multiple containers are involved construct temporary dikes of dirt, sand, or any appropriate readily available material to prevent spreading of the material. Close or plug hole in leaking container or turn container with leaking side up and transfer to another container. Keep from entering storm sewers and ditches which lead to waterways, and if necessary, call the local fire or police department for immediate emergency assistance.

CONTAINMENT AND CLEAN-UP MEASURES: Clean up with non-combustible absorbent (such as: sand, soil, and so on). Shovel up and place all spill residue in suitable containers. dispose of at an appropriate waste disposal facility according to current applicable laws and regulations and product characteristics at time of disposal (see Section 13 - Disposal Considerations). If necessary, neutralize using suitable buffering material, (acid with soda ash or base with phosphoric acid), and test area with litmus paper to confirm neutralization. Dispose of via a licensed waste disposal contractor.

Section 7: Handling and Storage

HANDLING: Use only as directed via manufacturer's instructions. Isolate from oxidizers, heat, & open flame. Use only with adequate ventilation. Avoid breathing of vapor. If necessary wear Self-Contained Breathing Apparatus or respirator. Avoid contact with skin & eyes. If any chance exist of contact with eyes or skin wear OSHA Standard goggles or face shield. Consult Safety Equipment Supplier. Wear goggles, face shield, gloves, apron & footwear impervious to material. Wash clothing before reuse. Empty container very hazardous! Follow all label precautions!

STORAGE: OSHA Flammable Category 3. Keep in fireproof surroundings. Keep separated from strong oxidants. Keep container tightly closed & upright when not in use to prevent leakage. Store containers in a cool, dry location, away from direct sunlight, sources of intense heat, or where freezing is possible. Store containers away from incompatible materials(see Section 10, Stability and Reactivity). Inspect all incoming containers before storage to ensure containers are properly labeled and not damaged. Post warning and "NO SMOKING" signs in storage and use areas, as appropriate. Empty containers should be handled with care.

EMPTY CONTAINER WARNING:

Empty containers may contain residue and can be dangerous. Do not attempt to refill or clean containers. DO NOT EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION.

Section 8: Exposure Controls/Personal Protection

CHEMICAL NAMES	CAS No.	EINECS No.	TWA (OSHA)	TLV (ACGIH)
Hydrodesulfurized naphtha	64742-82-1	265-185-4	No Data	No Data
Hydrotreated light distillate	64742-47-8	265-149-8	No Data	TLV: 200 mg/m3

Stoddard solvent	8052-41-3	232-489-3	PEL: 500 ppm	TLV: 100 ppm
medium aliphatic hydrocarbon	64742-88-7	232-455-8	100 ppm	100 ppm
Benzene, Ethylmethyl	25550-14-5	247-093-6	No Data	No Data
Trimethylbenzene	25551-13-7	247-099-9	No Data	TLV: 25 ppm

SDS FinalFinish

Date: 06/01/2016 Page 5 of 8

(Section 8 Continued)

Xylene {Benzene, dimethyl-}	1330-20-7	215-535-7	PEL: 100 ppm	TLV: 100 ppm STEL: 150 ppm
Trade Secret Polymer Resin Mixture	No Data	No Data	No Data	No Data

RESPIRATORY EXPOSURE CONTROL MEASURES: Maintain airborne contaminant concentrations below exposure limits given above. If respiratory protection is needed, use only protection authorized in 29 CFR 1910.134, European Standard EN 149, or applicable State regulations. If adequate ventilation is not available or there is potential for airborne exposure above the exposure limits, a respirator may be worn up to the respirator exposure limitations, check with respirator equipment manufacturer's recommendations/limitations. For a higher level of protection, use positive pressure supplied air respiration protection or Self-Contained Breathing Apparatus or if oxygen levels are below 19.5% or are unknown. Intentional misuse by deliberately concentrating and inhaling the contents can be harmful or fatal.

ENTRY INTO UNKNOWN CONCENTRATIONS OR IDLH CONDITIONS: Positive pressure, full-face piece Self-Contained Breathing Apparatus; or positive pressure, full-face piece Self-Contained Breathing Apparatus with an auxiliary positive pressure Self-Contained Breathing Apparatus.

VENTILATION LOCAL EXHAUST: Mechanical ventilation necessary for indoor use.

Please refer to ACGIH document, "Industrial Ventilation, A Manual of Recommended Practices", for details.

EYE PROTECTION: Splash goggles or safety glasses and face-shields are recommended when conditions exist that may lead to eye or skin contact.

HAND PROTECTION: Use gloves chemically resistant to this material. Preferred examples: Examples of acceptable glove materials include: Natural Rubber ("Latex"), Neoprene, Nitrile, or Vinyl . NOTICE: The selection of a specific glove should take into account the duration of use, the potential body reactions to glove materials, as well as the instructions/ specifications provided by the glove supplier.

BODY PROTECTION: If conditions exist that may lead to body contact use body protection appropriate for task. Cover-all, rubber aprons, or chemical protective clothing made from impervious materials are generally acceptable, depending on the task.

WORK & HYGIENIC PRACTICES: Provide readily accessible eye wash stations & safety showers. Wash at end of each shift & before eating, smoking or using the toilet. Remove clothing that becomes contaminated. Destroy contaminated leather articles. Launder or discard contaminated clothing.

Section 9: Physical and Chemical Properties

APPEARANCE: Brown Liquid

ODOR: Sweet/Petroleum Solvent

ODOR THRESHOLD: No data

pH (Neutrality): No data

MELTING POINT/FREEZING POINT: No data

BOILING RANGE (Initial Point, Dry Point): 300 - 395 F / 148 - 201 C

FLASH POINT : 101 F / 38 C

EVAPORATION RATE: No data

FLAMMABILITY CLASSIFICATION: Category 3 (OSHA)

LOWER FLAMMABLE LIMIT IN AIR (% by vol.): No data

UPPER FLAMMABLE LIMIT IN AIR (% by vol.): No data

VAPOR PRESSURE (mm of Hg)@20 C: 1.0

VAPOR DENSITY (air=1): Heavier than Air

DENSITY(@ 68 F / 20 C): No data

SPECIFIC GRAVITY: No data

WATER SOLUBILITY: None

PARTITION COEFFICIENT (n-Octane/Water): No data

AUTO IGNITION TEMPERATURE: No data
DECOMPOSITION TEMPERATURE: No data
VISCOSITY: Not Available
VOC WEIGHT: 49.1%
CHEMICAL STABILITY: Stable under normal conditions.
CONDITIONS TO AVOID: Isolate from oxidizers, heat, & open flame.

SDS FinalFinish

Date: 06/01/2016 Page 6 of 8

Section 10: Stability and Reactivity

MATERIALS TO AVOID & REACTIVITY: Reacts with strong oxidants, causing fire & explosion hazard. Avoid strong alkalis and acids. May attack or dissolve rubbers, plastics, adhesives, and low or non cross linked coatings.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide, Carbon Dioxide from burning.

HAZARDOUS POLYMERIZATION: Will not occur.

Section 11: Toxicological Information

ACUTE HAZARDS:

EYE & SKIN CONTACT: Primary irritation to skin, defatting, dermatitis. Primary irritation to eyes, redness, tearing, blurred vision. Liquid can cause eye irritation. Wash thoroughly after handling.

INHALATION: Anesthetic. Irritates respiratory tract. Acute over exposure can cause serious nervous system depression. Vapor harmful.

SWALLOWING: Harmful or fatal if swallowed. Swallowing can cause abdominal irritation, nausea, vomiting & diarrhea. The symptoms of chemical pneumonitis may not show up for a few days.

CONDITIONS AGGRAVATED: Persons with severe skin, liver or kidney problems should avoid use.

CHRONIC HAZARDS: Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Less than 1% of compounds (Trimethylbenzene, Xylene) are present that are rated by IARC and ACGIH as to possibility of being carcinogenic to humans.

IARC: Group 3, Inadequate in humans and inadequate or limited in animals

ACGIH: A4, Not classifiable as a human carcinogen: Agents which cause concern that they could be carcinogenic to humans but which cannot be assessed conclusively because of a lack of data. In vitro or animals studies do not provide indications of carcinogenicity which are sufficient to classify the agent into one of the other categories.

IRRITANT: This product is irritating to contaminated tissue.

NUMERICAL MEASURES OF TOXICITY: None Known

Section 12: Ecological Information

ENVIRONMENT: Do not allow into the environment.

PLANT AND ANIMAL HAZARDS: This product may be harmful or fatal to plant and animal life if released into the environment.

AQUATIC LIFE HAZARDS: The most sensitive known aquatic group to any component of this product is: Fish are adversely affected by components of this product. Environmental effects of the substance have not been investigated adequately.

AIR HAZARDS: Contains VOC's.

MOBILITY IN SOIL: This material is a mobile liquid.

DEGRADABILITY: This product is non-biodegradable.

Section 13: Disposal Considerations

The generation of waste should be avoided or minimized wherever possible.

Waste should not be disposed of into the sewer. If recycling of container is not possible use Incineration or landfill only in accordance with all federal, state, and local regulations.

SDS FinalFinish

Date: 06/01/2016 Page 7 of 8

(Section 8 Continued)

This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers. Empty containers and liners may retain some product residues. Vapor from some product residues may create a highly flammable or explosive atmosphere inside the container. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Do not dispose of on land, in surface waters, or in storm drains. Large amounts should be consigned to licensed hazardous waste haulers for disposal. Waste should be recycled or disposed of in accordance with all federal, state, and local regulations. Contact appropriate agency for requirements. Saturated materials should be allowed to dry with no wading, folding, or stacking to avoid excessive heat and possible spontaneous combustion.

Section 14: Transport Information

DOT/TDG: UN1263, Paint Related Material, Flammable liquid, Class 3, PG-III

IATA : UN1263, Paint Related Material, Flammable liquid, Class 3, PG-III
Refer to the current IATA regulations before shipping.

IMDG: UN1263, Paint Related Material, Flammable liquid, Class 3, PG-III

Shipper Note: Shipper is solely responsible for regulatory compliance in classification, packaging and labeling of shipments. Shipper must refer to the latest transport regulation in effect.

Section 15: Regulatory Information

EPA REGULATION:

SARA SECTION 311, 312

HAZARDS: Acute Health, Fire

This material contains no known products restricted under SARA Title III, Section 313 in amounts greater or equal to 1%.

Check state requirements. Exemption may exist if sold as a consumer product or hazardous substance, as those terms are defined in the Consumer Product Safety Act respectively, where the employer can demonstrate it is used in the work place in the same manner as normal consumer use, and which use results in a duration and frequency of exposure which is not greater than exposures experienced by consumers.

TSCA: All components of this material are listed on the TSCA Inventory or are exempt.

16: Other Information

Full text of R- and H- phrases shown in Section 3:

H312	Harmful in contact with skin
H315	Causes Skin Irritation
H317	May cause allergic skin reaction
H319	Causes serious eye irritation
H228	Flammable Solid

H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H336	May cause drowsiness or dizziness

SDS FinalFinish

Date: 06/01/2016 Page 8 of 8

(Section 16 Continued) Full text of R- and H- phrases shown in Section 3:

H350	May cause cancer
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H411	Toxic to aquatic life with long-lasting effects
R43	May cause sensitisation by skin contact
R46	May cause inheritable genetic damage
R65	Harmful: May cause lung damage if swallowed
R45	May cause cancer
Xn	Chemicals may cause damage to health
Eye Irrit. 2B	Serious eye damage / eye irritation, Category 2B
Skin Sens. 1	Sensitisation – Skin, Category 1
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Asp. Tox. 1	Aspiration hazard, Category 1
Acute Tox.4(Oral)	Acute Toxicity (Oral), Category 4
Acute Tox. 4 (Dermal)	Acute Toxicity (Dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute Toxicity (Inhalation), Category 4
STOT RE 1	Specific target organ toxicity – Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3,
Muta.Cat. 1	Chemicals that induce heritable genetic defects or increase their incidence
Carc.Cat.1;	Chemicals that may cause cancer or increase its incidence
Carc.Cat.2;	Carcinogen - Category 2
Aquatic Chronic 2	Hazardous to aquatic environment. Chronic Hazard, Category 2
Flam. Sol. 2	Flammable solids, Category 2
Resp. Sens. 1	Sensitisation – Respiratory, Category 1

HAZARD RATINGS:

HEALTH (NFPA): 1, HEALTH (HMIS): 2, FLAMMABILITY: 2, PHYSICAL HAZARD: 0
(Personal Protection Rating to be supplied by user based on use conditions.)

NOTICE:

Supplier makes no representations or warranties, either expressed or implied, of merchantability, fitness for a particular purpose with respect to the information set forth herein or to the product to which the information refers. Accordingly Supplier will not be responsible for damages resulting from use of or reliance upon this information. Users also assume all risks in regards to the use of, or reliance upon information contained herein. All information appearing herein is based upon data obtained from manufacturers and/or recognized technical sources. While the information is believed to be accurate, we make no representations as to its its comprehensiveness or accuracy. Individuals receiving this information must exercise their independent judgment in determining its appropriateness for a particular purpose.

Suppliers and users have the responsibility to comply with FEDERAL, STATE and COMMUNITY RIGHT TO KNOW regulations. Make this information available to any employee who requests it.

