

SAFETY DATA SHEET

Date Issued : 08/02/2019

SDS No : 12301

T-Max Zero VOC™

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: T-Max Zero VOC™**MANUFACTURER**

FinishFirst Auto Products
6700 NE 152nd Ave #200
Vancouver WA 98682

Customer Service: 800-998-9208**24 HR. EMERGENCY TELEPHONE NUMBER**

INFOTRAC: 1-800-535-5053

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS**Health:**

Flammable Liquids, Category 3
Skin Irritation, Category 2
Eye Irritation, Category 2A
Target Organ Toxicity (Single exposure), Category 3

GHS LABEL

Flame

Exclamation
mark**SIGNAL WORD: DANGER****HAZARD STATEMENTS**

H226: Flammable liquid and vapour.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H336: May cause drowsiness or dizziness.

PRECAUTIONARY STATEMENTS**Prevention:**

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.
P270: Do not eat, drink or smoke when using this product.
P240: Ground and bond container and receiving equipment.
P403+P233: Store in a well-ventilated place. Keep container tightly closed.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: WARNING! Flammable liquid and vapor. Eye, skin and respiratory tract irritant.
May be harmful if inhaled or absorbed through skin.

POTENTIAL HEALTH EFFECTS

EYES: Irritant. May cause redness, irritation and/or pain.

SKIN: May be harmful if absorbed through the skin. Irritant. May cause redness, inflammation or dermatitis.

T-Max Zero VOC™

INGESTION: May be irritating to digestive tract; may cause gastric distress, stomach pains.

INHALATION: May be harmful if inhaled. May cause respiratory tract irritation. May produce symptoms of central nervous system depression, including headache, dizziness, nausea, loss of balance, and drowsiness.

CARCINOGENICITY: Not listed as a carcinogen by the NTP, IARC, or OSHA.

MEDICAL CONDITIONS AGGRAVATED: No information found.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Vol. %	CAS
Benzene, 1-chloro-4-(trifluoromethyl)-	65 - 75	98-56-6
Acetone	25 - 35	67-64-1

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of water. Get medical attention, if irritation persists.

SKIN: Remove contaminated clothing/shoes. Flush skin with water for at least 15 minutes. Follow by washing with soap and water. If irritation occurs, get medical attention. Do not reuse clothing until cleaned.

INGESTION: If swallowed, DO NOT induce vomiting. Immediately give 2 glasses of water. Never give anything by mouth to an unconscious person. Call a physician.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

NOTES TO PHYSICIAN: All treatments should be based on observed signs and symptoms of distress in the patient. Consideration should be given to the possibility that overexposure to materials other than this product may have occurred. Treat symptomatically. No specific antidote available.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Foam, carbon dioxide, dry chemical.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Absorb liquid on vermiculite, floor absorbent, or other absorbent material, then place in container for chemical waste. Flush spill area with water spray. Prevent run-off from entering drains, sewers or streams.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Keep away from heat, sparks, and flame. Surfaces that are hot may ignite even liquid product in the absence of sparks or flame. Extinguish pilot lights, cigarettes and turn off other sources of ignition prior to use and until all vapors are gone. Use in well ventilated areas.

STORAGE: Store in a cool, dry, ventilated area, away from incompatible substances.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

T-Max Zero VOC™**EXPOSURE GUIDELINES**

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m ³
Acetone	OSHA PEL	TWA	1000	2400
	ACGIH TLV	TWA	500	
		STEL	750	

ENGINEERING CONTROLS: Local exhaust and general ventilation must be adequate to meet exposure limit(s).

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Chemical goggles/face shield.

SKIN: Gloves resistant to chemicals and petroleum distillates must be worn. Neoprene, butyl rubber, or polyethylene.

COMMENTS: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Faint aromatic hydrocarbon odor.

pH: Not determined.

PERCENT VOLATILE: 100

FLASH POINT AND METHOD: (-4°F) TAG CC

FLAMMABLE LIMITS: 0.9% to 12.8%

AUTOIGNITION TEMPERATURE: > 500°C

VAPOR PRESSURE: 185 mm Hg

VAPOR DENSITY: Heavier than air.

BOILING POINT: (133°F) to (282°F)

SOLUBILITY IN WATER: Slight

EVAPORATION RATE: 0.9

DENSITY: 9.82

VISCOSITY: Not specified.

(VOC): 0

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: Stable under normal conditions.

CONDITIONS TO AVOID: Oxidizing materials.

11. TOXICOLOGICAL INFORMATION**ACUTE TOXICITY**

Chemical Name	ORAL LD ₅₀
Acetone	5800 mg/kg (Rat)

T-Max Zero VOC™**DERMAL LD₅₀:** > 7426 mg/kg**ORAL LD₅₀:** 5800 mg/kg (rat)**INHALATION LC₅₀:** 76 mg/kg (4 hour), rat**12. ECOLOGICAL INFORMATION****AQUATIC TOXICITY (ACUTE)****48-HOUR EC₅₀:** 10.7 mg/l (Daphnia)**CHEMICAL FATE INFORMATION:** No data found for product.**13. DISPOSAL CONSIDERATIONS**

DISPOSAL METHOD: Product, as supplied, meets the characteristics of a ignitable hazardous waste as defined in 40 CFR 261.21-24. If mixed with other products, waste mixture must be characterized. **DO NOT** dispose of the product in drains or storm sewers. **DO NOT** dispose of this product in landfill without prior solidification. Waste product should be recycled whenever possible. Any disposal practice must be in compliance with federal, state, and local regulations. Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

EMPTY CONTAINER: **KEEP OUT OF REACH OF CHILDREN!** Empty containers retain product residue and can be dangerous. Contaminated packaging should be emptied as far as possible and after appropriate cleansing may be taken for reuse. Do not pressurize, cut weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks static electricity, or other sources of ignition.

RCRA/EPA WASTE INFORMATION: Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. US EPA guidelines for the classification determination are listed in 40 CFR.

Additionally, waste generators must consult state and local hazardous waste regulations to ensure complete and accurate classification.

14. TRANSPORT INFORMATION**DOT (DEPARTMENT OF TRANSPORTATION)****PROPER SHIPPING NAME:** Paint Related Material**PRIMARY HAZARD CLASS/DIVISION:** 3**UN/NA NUMBER:** UN 1263**PACKING GROUP:** III**NAERG:** 128**REPORTABLE QUANTITY (RQ) UNDER CERCLA:** Acetone: 5,000 lbs**LABEL:** Flammable liquid**15. REGULATORY INFORMATION****UNITED STATES****SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)****311/312 HEALTH CATEGORIES:** This product should be reported as a fire hazard.**313 REPORTABLE INGREDIENTS:** To the best of our knowledge, this product is not listed as a toxic chemical under Section 313 of SARA Title III.**TITLE III NOTES:** Parachlorobenzotrifluoride 98-56-6

T-Max Zero VOC™

Acetone 67-64-1

302/304 EMERGENCY PLANNING

EMERGENCY PLAN: To the best of our knowledge, this product is not listed as an extremely hazardous substance.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

CALIFORNIA PROPOSITION 65: To the best of our knowledge this material does not contain any chemicals known to the State of California to cause cancer, birth defects or other reproductive harm.

CANADA

DOMESTIC SUBSTANCE LIST (INVENTORY): Not Controlled.


16. OTHER INFORMATION

APPROVED BY: Compliance

PREPARED BY: Compliance **Date Prepared:** 08/02/2019

HMIS RATING

HEALTH	2
FLAMMABILITY	3
PHYSICAL HAZARD	0
PERSONAL PROTECTION	H

NFPA CODES

NFPA STORAGE CLASSIFICATION: These ratings are part of a specific hazard communication program and should be disregarded where individuals are not trained in the use of this hazard rating system. You should be familiar with the hazard communication programs applicable to your workplace.

HMIS RATINGS NOTES: The HMIS rating involves data interpretations that may vary from company to company. They are intended only for rapid, general identification of the magnitude of the specific hazard. To deal adequately with the safe handling of this material, all the information contained in the SDS must be considered. Personal protection rating to be supplied by user depending on use conditions.

MANUFACTURER DISCLAIMER: The information contained herein is based on the data available to us and is believed to be accurate. However, FinishFirst Auto Products, Inc makes no warranty, expressed or implied regarding the accuracy of this data or the results to be obtained from the use thereof. FinishFirst Auto Products, Inc assumes no responsibility for injuries from the use of the product described herein.